= 50mm Cordless Venetian



50mm Cordless Venetian

- · Rebated bottom-rail for easy grip to raise and lower by hand
- · Plastic tilt wand removes the need for a tie-off cleat
- · Cordless design meets child safety requirement

To Operate the Blind:

Always tilt the slats horizontally before raising or lowering the blind.

Only operate the tilt mechanism when the blind is fully down.



The rebated bottom-rail makes operating the blind easy

Our Econowood materials meets the following requirements:

ASTM F963-17, Section 4.3.5.2(2) (b)

Test method: ASTM International Standard ASTM F963-17, section 8.3.1 and Annex A7

25 1000 75 60 60 90 60 500

Hg

Pb

Sb Se

-	Unit	Result						
Test Item(s)	-	1001						
Parameter	-	-						
Total Arsenic (As)	mg/kg	ND						
Total Barium (Ba)	mg/kg	ND						
Total Cadmium (Cd)	mg/kg	ND						
Total Chromium (Cr)	mg/kg	ND						
Total Mercury (Hg)	mg/kg	ND						
Total Lead (Pb)	mg/kg	ND						
Total Antimony (Sb)	mg/kg	ND						
Total Selenium (Se)	mg/kg	ND						
Conclusion		PASS						

Ва

Cd Cr

Note / Kev :

Total Element(s)

Maximum Allowable Limit (mg/kg)

ND = Not detected ">" = Greather than mg/kg = miligram(s) per kliogram Detection Limit (mg/kg): "

NR = Not requested ppm = part(s) per million Detection Limit (mg/kg): "

= percent ## = mg/mg = miligram(s) per Nilogram | ppni - poni - poni

Fact Sheets:

- 1. Available in 50mm Econowood only
- 2. 5 colours available

Island White, Classic White, Drift White, Seashell, Parchment (refer to standard 50mm Econowood samples)

- 3. 53mm metal head-rail with 76mm Harbour Bridge Valance (face fit returns will only cover the side of head-rail unless sizes specified)
- 4. Width up to 2410mm

 Drop up to 2500mm, overall size up to 6.0m²
- 5. Color coordinated PVC wand control available in 610 and 1000mm length



MATERIALS & SIZES

· Available in 50mm Econowood only


STANDARD OPERATING SYSTEM


Cordless operation including wand tilter

STANDARD DEDUCTIONS

(Factory makes standard deductions deductions unless otherwise specified on order)

- Width deduction 10mm & drop 0mm (closed position) for inside mount
- Width and drop deductions 0mm for outside mount
- · Head-rail deduction 5mm (outside / face fit)





Face Fit

Reveal Fit

LIMITATIONS

- · Maximum width is 2410mm
- · Maximum drop is 2500mm
- Minimum width is 610mm
- Minimum drop is 600mm
- Single blind size should not exceed 6.0m²

Head-rail

• 53mm x 58mm High Profile Steel Head-rail

WAND TILTER

Material: PVC

Sizes: 610mm & 1000mm

VALANCE

76mm Harbour Bridge, maximum width 2510mm

Valance size based on head-rail size after deductions

- Reveal Fit extra 9mm
- Face Fit extra 20mm

Reveal Fit - no return ends Face Fit - returns to be nominated (eg right only, left only, left & right)

MINIMUM RECESS DEPTH (REVEAL)

- Fully recessed 65mm no returns required
- Semi recessed as requested. Note min returns is 20mm.

FACE FIT

- Standard returns 77m
- · Add for architrave depth if returning to the wall

COLOURS

Our standard colours are listed below

Blind colour	Ladder & Lift cord colour	Head-rail & bracket colour	Button colour
Island White Classic White Drift White	White	White	White
Seashell	Seashell	Seashell	Seashell
Parchment	Parchment	Parchment	Parchment

Cordless Venetian



53 x 58mm High Profile steel Head-rail



Box Bracket



Support Bracket for Head-rail



Wand Tilter



Ladder Cord



Valance Clip



Valance Return end Clip



Bottom-rail



76mm Harbour Bridge Valance



STANDARD TOLERANCE

Please note that our standard tolerance for blind width and blind drop is +/- 5mm. If the blind is made within our tolerance range, no claim will be accepted.




WARRANTY INFORMATION

Components: 3 years Colour: 2 years

LARGER SIZES

As a guide blinds over 4m² will be heavy to lift; it is advised to use two or more blinds on one head-rail to reduce lift load. When lifting larger blinds, the operator should guide the blind by holding the base rail as they are lifting it.


Due to memory retention, blinds should not be left in the up position for any extended length of time. If the blind warps as a result of this no claim will be accepted



LIGHT BLEED

All blinds allow light to pass around the sides of the blind. In addition, there will be small pin holes of light in each slat where the ladder cords pass through. Consider using face fit as an option rather than reveal fit to reduce light bleed at the sides.

This is not a blockout blind.



CLEANING / REGULAR CARE

Use a soft duster or non-coloured cleaning cloth.

Wipe gently with a damp cloth to remove dust or marks from the blind surface using a chemical free or mild detergent.

DO NOT rub or use any abrasive substances or solvent.

